

Soldering Gun

HAKKO 951·952 ESD SAFE
 SOLDERING GUN



- Available for your Hakko 701, 702B, or 937.
- Compact design and light weight.
- Easy positioning for the solder feeding.
- A variety of tip type.

Specifications

Model No.	951	952
Type	M	L
Power Consumption	50W (24V)	
Temperature Range	200-480°C	
Tip to Ground Resistance	< 2Ω	
Tip to Ground Potential	< 2mV (Typ.0.6mV)	
Heating Element	Ceramic Heater	
Standard Tip	900M-T-S10 (Shape-S10)	900L-T-B (Shape-B)
Standard Guide Nozzle	ø1.0mm (No.B2654)	
Usable Solder Dia.	ø0.6, 0.8, 1.0, 1.2, 1.6mm	
Cord	1.1m	
Dimensions (w/o cord)	170(W) x 180(H)mm	
Weight (w/o cord)	177g	187g

Packing List

Model Name	Contents
HAKKO 951	Soldering gun1
HAKKO 952	Soldering gun1

Optional Parts

Part No.	Name/Description
B2652	Guide nozzle/ø0.6mm ESD
B2653	Guide nozzle/ø0.8mm ESD
B2654	Guide nozzle/ø1.0mm ESD
B2655	Guide nozzle/ø1.2mm ESD
B2656	Guide nozzle/ø1.6mm ESD
C1437	Iron holder

Replacement Tips

Unit : mm

Medium For 951, 958

				Tip Out Dia ø6.5mm	
900M-T-B 900M-T-BF2*	Shape-B	900M-T-0.8C	Shape-0.8C	900M-T-2C 900M-T-2CF*	Shape-2C
900M-T-4C 900M-T-4CF*	Shape-4C	900M-T-1.6D	Shape-1.6D	900M-T-2.4D	Shape-2.4D
900M-T-K	Shape-K	900M-T-SB	Shape-SB	900M-T-S3	Shape-S3
900M-T-S10	Shape-S10	900M-T-S11	Shape-S11	900M-T-3C 900M-T-3CF*	Shape-3C
				900M-T-3.2D	Shape-3.2D
				900M-T-S4	Shape-S4

Large For 952, 959

				Tip Out Dia ø8.5mm	
900L-T-B	Shape-B	900L-T-2B	Shape-2B	900L-T-2C 900L-T-2CF*	Shape-2C
900L-T-4C 900L-T-4CF*	Shape-4C	900L-T-5C 900L-T-5CF*	Shape-5C	900L-T-2.4D	Shape-2.4D
900L-T-K	Shape-K	900L-T-S1	Shape-S1	900L-T-3C 900L-T-3CF*	Shape-3C
				900L-T-3.2D	Shape-3.2D

* These tips are tinned on the soldering surface only.
 * 900M-T-BF2 is tinned a distance of 2mm from the end of the tip.
 * For heavy duty soldering HAKKO recommends the 952 and the 959 gun with heavier tips.

CAUTION
 Use only genuine replacement tips for Hakko 951, 952, 958 and 959.
 The tips for Hakko Dash are not available to use.