

HAKKO 958·959

SOLDERING GUN ESD SAFE



- Easy one-hand soldering.
- Uniform soldering work.
- High-accuracy thermal control allows lead-free soldering.
- Thermal capacity can be selected according to the soldering applications.
- Space-saving design.

* Setting example: HAKKO 958, HAKKO 937 and HAKKO 373.
 (HAKKO 937, HAKKO 373 and the iron holder are sold separately.)

Setting Example

Soldering gun

M type : HAKKO 958



L type : HAKKO 959



* Select one.

Soldering station

HAKKO 701



HAKKO 937



HAKKO 702B



* Select one.

Solder-feeding unit

HAKKO 373



Solder dia.
adjustment ring



* Select one.

Option

Mounting plate No.B3270



* For 937 only.

Iron holder No.C1437



* Soldering gun is not included.

Specifications

Model No.	958	959
Type	M	L
Power Consumption	50W (24V)	
Temperature Range	200-480°C	
Tip to Ground Resistance	< 2Ω	
Tip to Ground Potential	< 2mV (Typ.0.6mV)	
Heating Element	Ceramic Heater	
Standard Tip	900M-T-B (Shape-B)	900L-T-B (Shape-B)
Tube Unit	S: Applicable solder dia. (ø0.6~1.0mm) L: Applicable solder dia. (ø1.2~1.6mm)	
Guide Nozzle	ø0.6, 0.8, 1.0, 1.2, 1.6mm	
Usable Solder Dia.	ø0.6, 0.8, 1.0, 1.2, 1.6mm	
Cord	1.1m	
Dimensions (w/o cord)	170(W) x 180(H) x 23(D)mm	
Weight (w/o cord and tube unit)	177g	187g

Replacement Tips

Please refer to page 26.

Packing List

Part No.	Contents
958-01	Soldering gun with guide nozzle (ø1.0mm-No.B2654) 1
	Guide nozzle (ø0.6mm-No.B2652, ø0.8mm-No.B2653) 2
	Tube unit S (No.B3268) 1
958-02	Soldering gun with guide nozzle (ø1.6mm-No.B2656) 1
	Guide nozzle (ø1.2mm-No.B2655) 1
	Tube unit L (No.B3269) 1
959-01	Soldering gun with guide nozzle (ø1.0mm-No.B2654) 1
	Guide nozzle (ø0.6mm-No.B2652, ø0.8mm-No.B2653) 2
	Tube unit S (No.B3268) 1
959-02	Soldering gun with guide nozzle (ø1.6mm-No.B2656) 1
	Guide nozzle (ø1.2mm-No.B2655) 1
	Tube unit L (No.B3269) 1

* When ordering HAKKO 958 or 959, please select the suitable model for your using solder wire diameter.

Optional Parts

Please refer to page 26.